



## **molift** QuickRaiser 205



Molift QuickRaiser 205 is a state of the art sit-to-stand hoist, with an **electrically adjustable leg base** and an **outstanding lifting capacity**. The standing hoist is comfortable, stable and safe with **exceptional manoeuvrability**. The unique wheel position, angled push bar and the extraordinary weight distribution of the base provides a **small turning radius** and easy manoeuvrability even in very narrow spaces. With the small castor option (Ø 50mm), it is only 7,5 cm high (3"), and fits under most beds and chairs while the electrically adjustable legs enables accessibility almost everywhere.

The Active Lifting Arm (four point spreader bar) and the RgoSling Active provides **extra support** when hoisting from sit to stand. The inclined column **encourages a natural pattern** of movement and fulfills the hoisting needs of users with some weight bearing capacity.



## **molift** QuickRaiser 205

### Features

**Ergonomic Design** Slanting column lifts the user up and forwards to imitate the natural movement pattern.

**Comfort, Safety and Stability** Active Lifting Arm (four point spreader bar) and the RgoSling Active provides extra support when hoisting from sit to stand.

**Automatic Warning** Annual periodic inspection/service.

**Easy to Manoeuvre** Easy to operate in moving and handling situations; toilet, sit-to-stand, stand-up training.

**NEW Operation Panel** and hand control provides intuitive and safe operation. Also includes a quick guide for sling application and safe use.

### Technical Facts

#### Item No.

29000 (Active 50/75mm)      29001 (Standup 50/75mm)  
29100 (Active 75/100mm)    29101 (Standup 75/100mm)

**Max User Weight** 205kg    **Total Weight** 44kg

**Chassis** 17kg    **Lifting Arm** 4.5kg    **Leg Support** 3.5kg

**Column** (heaviest part) 19kg

**Battery** SLA 24V    **Charge Time** 4hours

**No. of Lifts (75kg) with Fully Charged Battery** >100

**Lifting Speed** 3.5cm/s 75kg    3.0cm/s 205kg

**Lifting Range** 60cm

**Width of Wheelbase - External** 62cm - **Internal** 20cm

**Height of Wheelbase Castor Ø 75/50** 76mm

**Height of Wheelbase Castor Ø 100/75** 101mm

**Ground Clearance Castor Ø 75/50** 27mm

**Ground Clearance Castor Ø 100/75** 52mm

**Height of Footplate Castor Ø 75/50** 65mm

**Height of Footplate Castor Ø 100/75** 90mm

**Turning Radius** 115cm

**Cleaning Instructions** Use a solvent-free cleaning agent (ph Level 5-9) or with a 70% disinfectant solution. Can be decontaminated at max 85°C / 185°F

### Accessories

**Stand Up Lifting Arm** 2910061

Ideal to use with RgoSling Standup slings.

**Adjustable Leg Support** 2910055

The leg support is adjustable without tools.

**Inlays for Footplate** 2920151 set of 2

Inlays with slip resistant material to increase friction.